JULIA JULS40

Julia High Profile Three Hole Wall Mounted Lavatory Faucet with Metal Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 8 1/2"

Drain Assembly Materials: Brass Drain Depth Maximum: 2" Drain Depth Minimum: 1 1/2" Drain Hole Diameter: 1 3/4" Drain Style: Lift and Turn

Escutcheon Primary Material: Brass Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Handle Turn Angle: Quarter Turn Height: 6 1/4" Index Marking: H/C Inlet Connection Size: 1/2" Inlet Connection Type: Female NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Wall Mounted Length: 15"

Number Of Handles: Two Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: Y

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN JULIA HIGH PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES | JULS40

INSPIRATION

An interpretation of 1920s French country, Julia speaks to decoration and intricate design displayed through beautifully composed turnings. These details embody the robust, signature high profile spout enabling Julia to transition fluidly from informal to formal environments.

CODES & STANDARDS

JULS40X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Metal lever handles

Includes European size lift and turn drain

Features signature detail of the graceful, high profile swivel spout

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS





PRODUCT (NOTES)

Lift & Turn drain with overflow included. Rough required GUSV25R sold separately.

JULIA JULS40

Julia High Profile Three Hole Wall Mounted Lavatory Faucet with Metal Lever Handles

