# WATERWORKS

Ludlow LVS202

Ludlow Volta 10" Rain Showerhead with 18" Ceiling Mounted Shower Arm



# **TECHNICAL DETAILS**

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 32 mm Flow Restriction Options: 1.5, 1.75, 2.0 Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Pivot: Y Primary Material: Brass

Restricted Maximum Flow Rate: 6.6 liters/min Water Pressure Maximum: 6.0 bar

Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN LUDLOW VOLTA 10" RAIN SHOWERHEAD WITH 18" CEILING MOUNTED SHOWER ARM | LVS202

#### **INSPIRATION**

Our fresh take on American industrial design comes in three styles, each of them clean-lined, and distinct to Waterworks.

#### **CODES & STANDARDS**

LVS202X, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), WaterSense(1.5GPM, 1.75GPM & 2.0GPM Only), DOE, State of MA

### **PRODUCT FEATURES**

Made of Brass

Features a swivel 10" rain showerhead with easy clean rubber nozzles

Includes an 18" ceiling mounted shower arm

Stocked in Brass, Chrome, Nickel and Matte Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate

# **CERTIFICATIONS**






# PRODUCT (NOTES)

Ludlow LVS202

Ludlow Volta 10" Rain Showerhead with 18" Ceiling Mounted Shower Arm



STYLE NO.	DIM "A"	DIM "B"
LVS200	10 <sup>5</sup> / <sub>16</sub> " [261mm]	6 <sup>9</sup> / <sub>16</sub> " [167mm]
PTS200		
LVS201	16 <sup>5</sup> / <sub>16</sub> " [414mm]	12 <sup>9</sup> / <sub>16</sub> " [319mm]
PTS201		
LVS202	22 <sup>5</sup> / <sub>16</sub> " [566mm]	18 <sup>9</sup> / <sub>16</sub> " [472mm]
PTS202		

CEILING VIEW SCALE: 3"=1'-0"

