WATERWORKS studio

TRANSIT

TR01TF

Transit Deck Mounted Low Profile Concealed Tub Filler with Metal Handshower and Metal Cross Handles



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 37 mm Deck Thickness Minimum: 10 mm Diameter of Head: 56 mm Escutcheon Primary Material: Brass Fittings Hole Diameter: 38 mm Flow Restriction Options: 1.75, 1.5 Handle Spread Maximum: 305 mm Handle Spread Minimum: 254 mm Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 2.0 m Depth / Width: 252 mm Height: 187 mm Index Marking: Blank Inlet Connection Size: 3/4" Inlet Connection Type: Male G/BSPP Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 254 mm Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Length: 445 mm Number of Handles: Two Number of Holes: Four Hole Pivot: N Primary Material: Brass Restricted Maximum Flow Rate: 7.6 liters/min Spout Reach: 8" Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 5.5 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

INSPIRATION

Stylish simplicity that fits into any decor. Each design represents a sophisticated mix of modern and traditional influences, streamlined into a sculpted and tapered look.

PRODUCT FEATURES

Cross Handles

This item is stocked in a Chrome, Nickel and Unlacquered Brass finishes.

Standard flow rate 2.ogpm. Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

WATERWORKS studio

TRANSIT

TR01TF

Transit Deck Mounted Low Profile Concealed Tub Filler with Metal Handshower and Metal Cross Handles

