EASTON

ELS32B

Easton Wall Mounted Lavatory Faucet with Night Lever Handle



SHOWN IN EASTON WALL MOUNTED LAVATORY FAUCET WITH NIGHT LEVER HANDLE | ELS32B

TECHNICAL DETAILS

Drain Depth Maximum: 51 mm
Drain Depth Minimum: 10 mm
Drain Hole Diameter: 38 mm
Drain Style: Push Touch
Fittings Hole Diameter: 35 mm
Handle Spread Maximum: 203 mm
Handle Spread Minimum: 203 mm
Handle Turn Angle: Quarter Turn
Inlet Connection Size: 1/2"
Inlet Connection Type: Female NPT
Restricted Maximum Flow Rate: 4.5 liters/min
Water Pressure Maximum: 6.0 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

Rooted in classical Edwardian design, Easton is our most expansive collection—offering a comprehensive family of pieces that bring polished detail and timeless tradition to any setting. Revered for its exquisite proportions and impeccable scale, Easton is a trusted choice among designers.

CODES & STANDARDS

ELS32B-F.RX, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, WaterSense(1.0GPM and 1.2GPM Only), CEC, DOE

PRODUCT FEATURES

Earthenware Lever Handles

Includes Universal Lift and Turn Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Available in 1.2gpm (4.5L/min) flow rate.

Includes interchangeable indices, with the Waterworks logo installed as standard and a complementary set of "H" & "C" indices presented in a velvet pouch, allowing you to tailor the look to your space.
Stocked in Nickel and Brass


CERTIFICATIONS

PRODUCT (NOTES)


EASTON

ELS32B


Easton Wall Mounted Lavatory Faucet with Night Lever Handle




TOP VIEW SCALE: 1½"=1'-0"





ADAPTER INCLUDED - INTERNATIONAL USE ONLY





FRONT VIEW SCALE: 1½"=1'-0"





SIDE VIEW SCALE: 1½"=1'-0"