Ludlow LDXT60

Ludlow Floor Mounted Exposed Tub Filler with Handshower and Cross Handles



SHOWN IN LUDLOW FLOOR MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND CROSS HANDLES | LDXT60

# TECHNICAL DETAILS

ADA Compliance: No

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 276 mm
Diameter Of Head: 52 mm
Diameter Of Legs Tubes: 37 mm
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 32 mm
Flow Restriction Options: 1.5, 1.75, 2.0
Handle Spread Maximum: 203 mm
Handle Spread Minimum: 203 mm
Handle Turn Angle: Quarter Turn
Handshower Spray Hose Length: 1.7 m

Height: 968 mm

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 203 mm Inlet Supply Spread Minimum: 203 mm

Installation Type: Freestanding

Integrated Diverter: N Integrated Spray: N Length: 368 mm

Number Of Handles: Two Number Of Holes: Two Hole

Pivot: N

Primary Material: Brass Spout Swivel: N Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

### **INSPIRATION**

Our fresh take on American industrial design features comes in two styles, each of them clean-lined, versatile and unique to Waterworks. Choose from original Ludlow, featuring a square plate and exposed screws, and Ludlow Volta, with a round escutcheon for a softer, more transitional feel.

#### **CODES & STANDARDS**

LDXT60X, ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection, CEC, DOE, State of MA

## PRODUCT FEATURES

Features All Metal Cross Handles

Diverter handle allows bather to move water from spout to handshower

The Handshower offers a fixed spray pattern

Stocked in Chrome, Nickel and Brass

Unrestricted flow for tub spout. Handshower available in 1.75gpm (6.6L/min) flow rate

## **CERTIFICATIONS**





#### PRODUCT (NOTES)

Ludlow LDXT60

Ludlow Floor Mounted Exposed Tub Filler with Handshower and Cross Handles

