
DEWEY SCONCE

STYLE No. DWLT01 [DW01LT]

Wall Mounted Single Arm Sconce with Fabric Shade



* All items in [BRACKETS] refer to UK styles

SPECIFICATIONS:

Bulb Base Size: E14 Bulb Type: Candelabra

Junction Box Orientation: Vertical Junction Box Size: Gem Box **Max** Wattage: 60 Watt

Orientation: Up Shade Material: Silk Voltage: 120 [240] Required Electrical Feeds:

US: Black "Hot" wire; White "Neutral" wire; Green or Bare

"Ground" wire

UK: [Brown "Line" wire; Blue "Neutral" wire; Green/

YellowStriped or Bare "Earth" wire]

IMPORTANT:

- WARNING: The power supply must be turned off prior to installation. Turn off the main electrical supply to the junction box from the fuse box/circuit breaker. Turning power off at the switch is not sufficient.
- To ensure this product is installed properly, you must read and follow these guidelines.
- The owner/user of this product must keep this information for future reference.
- DWLT01 is U.L. certified and is suitable for damp or dry locations. The U.L. listing mark can be found on the inside of the cover plate.
- DW01LT are CE rated. Proof of CE compliance will be provided upon request.
- Be sure your installation conforms to federal state, and local CODES.

Installation Guidelines

- This product must be installed by a professional licensed electrical contractor.
- Refer to the specification and assembly drawings attached. Product is sold partially assembled but shown fully disassembled for illustrative and service purposes only.
- > Max wattage for DWLT01 [DW01LT] is 60 watts forincandescent Candelabra base light bulbs.

SCONCE INSTALLATION:

- REQUIRED: Install a Gem Box electrical junction box at the desired height.
- See Figure 01 for Steps 1 2.




FIGURE - 01

- Remove the MOUNTING PLATE by unthreading the SET SCREW from the back plate.
- Pull the wires in the JUNCTION BOX through the center hole of the MOUNTING PLATE. Attach the MOUNTING PLATE to the JUNCTION BOX using the MOUNTING SCREWS making sure to keep the proper alignment of the plate.
- > See Figure 02 for Steps 3 6.

These guidelines have been prepared for the professional contractor to aid in the installation of: DWLT01 [DW01LT]). All dimensions are based on original specification and are subject to change and variation. PLEASE CONSULT YOUR DESIGN ASSOCIATE FOR CURRENT SPECIFICATIONS.

WATERWORKS

Installation Guidelines

SERVICING THE LIGHT:

- See Figure 03 for Step 7.
- Lift the SHADE to gain access to the BULB for cleaning and servicing.
- 8. If further assistance is required, please contact Product Support at 1-800-927-2120 (8am-6pm EST).




FIGURE - 03




FIGURE - 02

- Fasten the bare copper fixture wire to the green or bare copper wire in the box with a wire nut or fasten it to the MOUNTING PLATE with the ground screw provided.
- 4. Fasten the white fixture wire to the white wire in the box with a wire nut. Tightly wrap the connection with electrical tape beginning 1" [25mm] below the wire nut to ensure the tape seals the end of the nut. Make sure that there are no exposed wires that could cause ashort circuit.
- Repeat previous step with the black fixture wire and the black wire from the junction box. Make sure the wires are pushed into the junction box.
- Attach the LIGHT ASSEMBLY to the MOUNTING PLATE on the wall by reinserting the SET SCREW.

These guidelines have been prepared for the professional contractor to aid in the installation of: DWLTOI [DWOILT]) All dimensions are based on original specification and are subject to change and variation. PLEASE CONSULT YOUR DESIGN ASSOCIATE FOR CURRENT SPECIFICATIONS.

WATERWORKS