HENRY HNLS01

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



SHOWN IN HENRY LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES | HNLS01

TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 1 5/8"

Deck Thickness Minimum: 3/16"

Depth/Width: 7 5/8"

Drain Depth Maximum: 2 5/8" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 3/4" Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 1/4" Handle Spread Maximum: 12" Handle Spread Minimum: 8"

Handle Turn Angle: Quarter Turn

Height: 3 5/8"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut

Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8"

Installation Type: Deck Mounted

Integrated Diverter: N

Integrated Spray: N Number Of Handles: Two

Number Of Holes: Three Hole

Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Spray Included In Unit: N Suggested Application: Bath

Valve Material: Ceramic Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

NSF/ANSI/CAN 61:Q < 1, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Metal cross handles

Includes European-size push touch drain

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

HENRY HNLS01

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

