Henry HNLS01

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



SHOWN IN HENRY LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES | HNLS01

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 41 mm Deck Thickness Minimum: 5 mm

Depth/Width: 194 mm

Drain Depth Maximum: 67 mm
Drain Depth Minimum: 10 mm
Drain Hole Diameter: 44 mm
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 32 mm
Handle Spread Maximum: 305 mm
Handle Spread Minimum: 203 mm
Handle Turn Angle: Quarter Turn

Height: 92 mm

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 203 mm Installation Type: Deck Mounted

Integrated Diverter: N Integrated Spray: N Number Of Handles: Two Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 4.5 liters/min

Spout Swivel: N

Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 6.0 bar

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

CODES & STANDARDS

NSF/ANSI/CAN 61:Q < 1, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Metal cross handles

Includes European-size push touch drain

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

Henry HNLS01

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

