

BOND

BKM12B

Bond Tandem Series One Hole Gooseneck Integrated Pull
Spray Kitchen Faucet with Two-Tone Lever Handle



SHOWN IN BOND TANDEM SERIES ONE HOLE GOOSENECK INTEGRATED PULL SPRAY KITCHEN FAUCET WITH TWO-TONE LEVER
HANDLE | BKM12B

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable Versus Fixed Spray: Adjustable
Deck Thickness Maximum: 2 1/4"
Deck Thickness Minimum: 1/4"
Fittings Hole Diameter: 1 1/2"
Handle Turn Angle: Tilt and Turn
Handshower Spray Hose Length: 59"
Inlet Connection Size: 3/8"
Inlet Connection Type: Compression Connection Hoses
Integrated Diverter: Y
Restricted Maximum Flow Rate: 1.75 gpm
Spout Swivel: Y
Spray Included In Unit: Y
Valve Material: Ceramic
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 25.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

PRODUCT FEATURES

Lever Handle

Two Function Integrated Pull Spray operated by a sliding button, switches from aerated stream to jet spray. The button returns to aerated stream when disengaged and remains in spray mode without holding down
Features Two-Tone Handle

Stocked in Nickel and Brass

Available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS

PRODUCT (NOTES)

BOND

BKM12B

Bond Tandem Series One Hole Gooseneck Integrated Pull
Spray Kitchen Faucet with Two-Tone Lever Handle

