

EASTON

ELS3R2

Easton Wall Mounted Lavatory Faucet with Royal Delft Rake Lever Handle



SHOWN IN EASTON WALL MOUNTED LAVATORY FAUCET WITH ROYAL DELFT RAKE LEVER HANDLE | ELS3R2

TECHNICAL DETAILS

Drain Depth Maximum: 51 mm
 Drain Depth Minimum: 10 mm
 Drain Hole Diameter: 38 mm
 Drain Style: Push Touch
 Fittings Hole Diameter: 35 mm
 Handle Spread Maximum: 203 mm
 Handle Spread Minimum: 203 mm
 Handle Turn Angle: Quarter Turn
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Female NPT
 Restricted Maximum Flow Rate: 4.5 liters/min
 Water Pressure Maximum: 6.0 bar
 Water Pressure Minimum: 1.5 bar
 Water Pressure Recommended: 3.0 bar

INSPIRATION

Rooted in classical Edwardian design, Easton is our most expansive collection—offering a comprehensive family of pieces that bring polished detail and timeless tradition to any setting. Revered for its exquisite proportions and impeccable scale, Easton is a trusted choice among designers.

CODES & STANDARDS

ELS3R2-F.RX, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, WaterSense(1.0GPM and 1.2GPM Only), CEC, DOE

PRODUCT FEATURES

Royal Delft Handpainted Earthenware Lever Handles

Includes Universal Lift and Turn Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Available in 1.2gpm (4.5L/min) flow rate.

Includes interchangeable indices, with the Waterworks logo installed as standard and a complementary set of "H" & "C" indices presented in a velvet pouch, allowing you to tailor the look to your space.

Stocked in Nickel and Brass

CERTIFICATIONS




PRODUCT (NOTES)

EASTON


ELS3R2

Easton Wall Mounted Lavatory Faucet with Royal Delft Rake
Lever Handle




TOP VIEW

SCALE: 1 1/2\"=1'-0"




ADAPTER INCLUDED -
INTERNATIONAL USE ONLY



FRONT VIEW

SCALE: 1 1/2\"=1'-0"



SIDE VIEW

SCALE: 1 1/2\"=1'-0"

