Boulevard BDS180

Boulevard 8" Rain Showerhead with 6" Ceiling Mounted Shower Arm



# **TECHNICAL DETAILS**

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 32 mm Flow Restriction Options: 1.5, 1.75, 2.0 Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Pivot: Y Primary Material: Brass

Restricted Maximum Flow Rate: 6.6 liters/min Water Pressure Maximum: 6.0 bar

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN BOULEVARD 8" RAIN SHOWERHEAD WITH 6" CEILING MOUNTED SHOWER ARM | BDS180

### **INSPIRATION**

Inspiration from 1930s objects evokes extravagance: a strong silhouette, lavish scale and elegant decoration. Machine and artisan hands yield crisp details and curves.

### **CODES & STANDARDS**

BDS180X, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), WaterSense(1.5GPM, 1.75GPM & 2.0GPM Only), DOE, State of MA

## **PRODUCT FEATURES**

Made of Brass

Features a swivel 8" rain showerhead with easy clean rubber nozzles

Includes a 6" ceiling mounted shower arm

Stocked in Brass, Chrome, Nickel and Matte Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate

# **CERTIFICATIONS**





# PRODUCT (NOTES)

Boulevard BDS180

Boulevard 8" Rain Showerhead with 6" Ceiling Mounted Shower Arm

