WATERWORKS

BOND BKM120

Bond Solo Series One Hole Gooseneck Integrated Pull Spray Kitchen Faucet with Straight Lever Handle



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Adjustable

Deck Thickness Maximum: 2 1/4" Deck Thickness Minimum: 1/4" Fittings Hole Diameter: 1 1/2" Handle Turn Angle: Tilt and Turn Handshower Spray Hose Length: 59"

Inlet Connection Size: 3/8"

Inlet Connection Type: Compression Connection Hoses

Integrated Diverter: Y

Restricted Maximum Flow Rate: 1.75 gpm

Spout Swivel: Y

Spray Included In Unit: Y Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 25.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

BKM120X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, State of MA

PRODUCT FEATURES

Lever Handle

Two Function Integrated Pull Spray operated by a sliding button, switches from aerated stream to jet spray. The button returns to aerated stream when disengaged and remains in spray mode without holding down

Stocked in Chrome, Nickel, Brass and Dark Nickel

CERTIFICATIONS



PRODUCT (NOTES)

BOND BKM120

Bond Solo Series One Hole Gooseneck Integrated Pull Spray Kitchen Faucet with Straight Lever Handle

