

Bond

BKM12D

Bond Union Series One Hole Gooseneck Integrated Pull Spray Kitchen Faucet with Enamel Guilloche Lines Lever Handle



SHOWN IN BOND UNION SERIES ONE HOLE GOOSENECK INTEGRATED PULL SPRAY KITCHEN FAUCET WITH ENAMEL GUILLOCHE LINES LEVER HANDLE | BKM12D

TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable Versus Fixed Spray: Adjustable
Deck Thickness Maximum: 57 mm
Deck Thickness Minimum: 6 mm
Fittings Hole Diameter: 38 mm
Handle Turn Angle: Tilt and Turn
Handshower Spray Hose Length: 1.5 m
Inlet Connection Size: 3/8"
Inlet Connection Type: Compression Connection
Hoses
Integrated Diverter: Y
Restricted Maximum Flow Rate: 6.6 liters/min
Spout Swivel: Y
Spray Included In Unit: Y
Valve Material: Ceramic
Water Pressure Maximum: 6.0 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

PRODUCT FEATURES

Lever Handle

Two Function Integrated Pull Spray operated by a sliding button, switches from aerated stream to jet spray. The button returns to aerated stream when disengaged and remains in spray mode without holding down

Features Guilloche Lines combined with Enamel Handle

Stocked in Nickel and Brass

Available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS

PRODUCT (NOTES)

Bond

BKM12D

Bond Union Series One Hole Gooseneck Integrated Pull
Spray Kitchen Faucet with Enamel Guilloche Lines Lever
Handle

