## WATERWORKS

RWKM50 R.W. ATLAS

R.W. Atlas Three Hole High Profile Kitchen Faucet with Metal Side Mount Lever Handles and Spray



SHOWN IN R.W. ATLAS THREE HOLE HIGH PROFILE KITCHEN FAUCET WITH METAL SIDE MOUNT LEVER HANDLES AND

### **INSPIRATION**

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

#### **PRODUCT FEATURES**

Features side mount lever handles with tumbled barrels marked with an engraved H and C. Integrated side spray allows for mixed water and features knurled detail on handle. Meets or exceeds the Weighted Average Lead Requirements of 0.25%.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in high efficiency flow options. Contact a sales associate for details.

#### **TECHNICAL DETAILS**

Deck Thickness Maximum: 41 mm Deck Thickness Minimum: 6 mm Escutcheon Primary Material: Brass Fittings Hole Diameter: 35 mm Flow Restriction Options: 2.0, 1.75, 1.5 Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 1.2 m Depth / Width: 300 mm Height: 259 mm Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Length: 537 mm Number of Handles: Two Primary Material: Brass Restricted Maximum Flow Rate: 8.3 liters/min Spout Swivel: Y Spray Included in Unit: Y Suggested Application: Bar, Kitchen, Laundry Valve Material: Ceramic Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar

Water Pressure Recommended: 3.0 bar

Adjustable versus Fixed Spray: Fixed Spray

#### **CERTIFICATIONS**



# R.W. ATLAS RWKM50

R.W. Atlas Three Hole High Profile Kitchen Faucet with Metal Side Mount Lever Handles and Spray

