Easton EAXT24

Easton Classic Exposed Tub Filler, Black Porcelain Handshower and Lever Diverter



SHOWN IN EASTON CLASSIC EXPOSED TUB FILLER, BLACK PORCELAIN HANDSHOWER AND LEVER DIVERTER | EAXT24

TECHNICAL DETAILS

ADA Compliance: No

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 171 mm
Flow Restriction Options: 1.75
Handle Spread Maximum: 184 mm
Handle Spread Minimum: 184 mm
Handle Turn Angle: Quarter Turn
Handshower Spray Hose Length: 1.5 m

Height: 394 mm

Index Color Finish And Material: White Porcelain

Inlet Connection Size: 3/4"

Inlet Connection Type: Female Union Nut Inlet Supply Spread Maximum: 184 mm Inlet Supply Spread Minimum: 184 mm Installation Type: Wall or deck mounted

Integrated Diverter: Y Length: 279 mm Primary Material: Brass

Restricted Maximum Flow Rate: 6.6 liters/min

Suggested Application: Bath Water Pressure Maximum: 5.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

EAXT24X, ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection, CEC, DOE, State of MA

PRODUCT FEATURES

Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Unions sold separately - UNUN60 (Floor Union), EAUN16 (Deck Union) and EAUN18 (Wall Union)

Unrestricted flow for tub spout. Handshower available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS





PRODUCT (NOTES)

Easton EAXT24

Easton Classic Exposed Tub Filler, Black Porcelain Handshower and Lever Diverter

