

## FLYTE

Flyte Floor Mounted Tub Spout

FLTS90



SHOWN IN FLYTE FLOOR MOUNTED TUB SPOUT | FLTS90

### TECHNICAL DETAILS

ADA Compliance: Yes  
 Adjustable versus Fixed Spray: Fixed Spray  
 Diameter of Legs / Tubes: 1 3/16"  
 Escutcheon Primary Material: Brass  
 Fittings Hole Diameter: 1 1/4"  
 Depth / Width: 12 3/8"  
 Height: 30 3/8"  
 Inlet Connection Size: 3/4"  
 Inlet Connection Type: Copper Sweat  
 Installation Type: Freestanding  
 Integrated Diverter: N  
 Integrated Spray: N  
 Length: 3 9/16"  
 Number of Holes: One Hole  
 Pivot: N  
 Primary Material: Brass  
 Spout Swivel: N  
 Spray Included in Unit: N  
 Suggested Application: Bath  
 Water Pressure Maximum: 85.0 psi  
 Water Pressure Minimum: 20.0 psi  
 Water Pressure Recommended: 45.0 psi

### INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

### CODES & STANDARDS

Code # FLTS90: Complies with ASME A112.18.1/CSA B125.1, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, and State of MA.

### PRODUCT FEATURES

Floor Mounted

This item is stocked in a Chrome and Nickel finishes.

Unrestricted flow of approximately 12 gallons per minute (gpm).

### CERTIFICATIONS



## FLYTE

Flyte Floor Mounted Tub Spout

FLTS90

