FLYTE FLLS60

Flyte Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Cross Handles and Valve



TECHNICAL DETAILS

ADA Compliance: Yes

Drain Assembly Materials: Brass Drain Depth Maximum: 2" Drain Depth Minimum: 1 1/4" Drain Hole Diameter: 1 1/2" Drain Style: USA Push Touch Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Height: 2 7/8"

Inlet Connection Size: 1/2"

Inlet Connection Type: Female NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8"

Length: 10 3/8"

Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm Valve Material: Brass, Ceramic Water Pressure Maximum: 80.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN FLYTE LOW PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES AND VALVE | FLLS60

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

Code # FLLS60: CEC

PRODUCT FEATURES

Push touch USA style drain included.

This item is stocked in a Chrome and Nickel finishes.

Cross Handles

Standard flow rate is 1.2gpm (4.5 L/min) and meets State of California requirements. Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS

PRODUCT (NOTES)

WATERWORKS

FLYTE	FLLS60
Flyte Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Cross Handles and Valve	