HENRY CHRONOS

CLS101

Henry Chronos Lavatory Faucet with Cross Handles



TECHNICAL DETAILS

ADA Compliance: Yes

Deck Thickness Maximum: 1 9/16" Deck Thickness Minimum: 5/16" Drain Depth Maximum: 2" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 1/2" Drain Style: Push Touch Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2 Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut

Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Valve Material: Brass and Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY CHRONOS LAVATORY FAUCET WITH CROSS HANDLES | CLS101

INSPIRATION

Inspired by dive watches, Henry Chronos radiates design prowess and technical precision. Chronos retains the design integrity of our original, iconic Henry collection, while imbuing it with modern details and exquisite materials.

CODES & STANDARDS

CLS101X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, DOE, State of MA

PRODUCT FEATURES

Features All Metal Cross Handles

Includes a Universal Push Touch Drain Sized to Fit US and Euro Sink Drain Openings

Stocked in Brass, Chrome and Nickel

Available in 1.2gpm (4.5L/min) Flow Rate

CERTIFICATIONS






PRODUCT (NOTES)

HENRY CHRONOS


CLS101


Henry Chronos Lavatory Faucet with Cross Handles



TOP VIEW

SCALE: 1/2"=1'-0"





SIDE VIEW

PRODUCT SUPPORT 800.927.2120 OPT 2 | WATERWORKS.COM SCALE: 1/5"=1'-0"