Bond BXT27S

Bond Rally Series Deck Mounted Exposed Tub Filler with Handshower and Lever Handles



INSPIRATION

Bond draws inspiration from the Aesthetic Movement, rare vintage lighters, and modern industrial design. The result is a contemporary collection with a soulful quality that inhabits the full range of modern style, from austere minimalism to warm contemporary.

TECHNICAL DETAILS

ADA Compliance: No

Deck Thickness Maximum: 51 mm Deck Thickness Minimum: 6 mm Diameter Of Legs Tubes: 32 mm Fittings Hole Diameter: 35 mm Handle Spread Maximum: 203 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 1.5 m Inlet Connection Size: 3/4"

Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 318 mm Inlet Supply Spread Minimum: 318 mm

Integrated Diverter: Y Number Of Holes: Two Hole Primary Material: Brass Spout Swivel: N Spray Included In Unit: Y Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

CODES & STANDARDS

ASME A112.18.1/CSA B125.1, CEC, State of MA, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection, NOM-012, WRAS

PRODUCT FEATURES

Lever Handles

Diverter knob allows bather to move water from spout to handshower. Handshower features 2-1/8" head with rubber nozzles.

Features a Sport Black Finish, smooth and velvety to the touch

Stocked in Chrome/Sport Black

Unrestricted flow for tub spout. Handshower available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

Bond BXT27S

Bond Rally Series Deck Mounted Exposed Tub Filler with Handshower and Lever Handles

