

LUDLOW

Ludlow Shinola Edition Floor Mounted Exposed Tub Filler with Handshower and Two-Tone Lever Handles

LDXTSE



TECHNICAL DETAILS

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Diameter of Head: 52 mm
Diameter of Legs / Tubes: 37 mm
Fittings Hole Diameter: 32 mm
Flow Restriction Options: 2.0, 1.75, 1.5, 0.92
Handle Spread Maximum: 203 mm
Handle Spread Minimum: 203 mm
Handle Turn Angle: Quarter Turn
Handshower / Spray Hose Length: 1.7 m
Depth / Width: 276 mm
Height: 968 mm
Inlet Connection Size: 3/4"
Inlet Connection Type: Copper Sweat
Inlet Supply Spread Maximum: 203 mm
Inlet Supply Spread Minimum: 203 mm
Integrated Diverter: Y
Length: 429 mm
Number of Handles: Two
Primary Material: Brass
Spout Swivel: N
Spray Included in Unit: Y
Valve Material: Ceramic
Water Pressure Maximum: 6.0 bar
Water Pressure Minimum: 1.5 bar
Water Pressure Recommended: 3.0 bar

INSPIRATION

A touch of classic Americana. Our fresh take on iconic industrial design has clean lines and dimensional details.

CODES & STANDARDS

Code # LDXTSE: Complies with ASME A112.18.1/CSA B125.1, ADA.
Certified with IAPMO, cUPC.

CERTIFICATIONS



