

FLYTE

Flyte Thermostatic Control Valve Trim with Metal Cross Handle

FLTH01



SHOWN IN FLYTE THERMOSTATIC CONTROL VALVE TRIM WITH METAL CROSS HANDLE | FLTH01

TECHNICAL DETAILS

ADA Compliance: Yes
 Control Valve Rough-in Depth Maximum: 108 mm
 Control Valve Rough-in Depth Minimum: 83 mm
 Diverter Valve Rough-in Depth Maximum: 108 mm
 Diverter Valve Rough-in Depth Minimum: 83 mm
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 114 mm
 Depth / Width: 67 mm
 Height: 140 mm
 Integrated Diverter: N
 Integrated Spray: N
 Length: 140 mm
 Number of Handles: One
 Pivot: N
 Primary Material: Brass
 Spout Swivel: N
 Spray Included in Unit: N
 Suggested Application: Bath

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

Code # FLSV01: Complies with ASME A112.18.1/CSA B125.1, ASTM E 1621-05, ANSI A117.1 ADA. Certified with IAPMO, cUPC & State of MA

PRODUCT FEATURES

Cross Handles

A solid brass trim plate features engraved graphic TEMPERATURE along with H and C markings

Requires 1/2" valve rough GUTH56 (USA) or GU56TH (UK) sold separately

Allows bather to adjust temperature of all waterway outlets, features anti-scald protection through an integrated high limit safety stop

This item is stocked in a Chrome, Nickel, and Graphite finishes

CERTIFICATIONS



PRODUCT (NOTES)

Requires 1/2" valve rough GUTH56 (USA) or GU56TH (UK) sold separately

FLYTE

FLTH01

Flyte Thermostatic Control Valve Trim with Metal Cross Handle

