Henry Chronos CNS357

Henry Chronos 5" Showerhead with Adjustable Spray with 12" Wall Mounted 90 Degree Shower Arm



TECHNICAL DETAILS

Fittings Hole Diameter: 35 mm Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT

Pivot: Y

Restricted Maximum Flow Rate: 6.6 liters/min

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN HENRY CHRONOS 5" SHOWERHEAD WITH ADJUSTABLE SPRAY WITH 12" WALL MOUNTED 90 DEGREE SHOWER ARM | CNS357

INSPIRATION

Inspired by dive watches, Henry Chronos radiates design prowess and technical precision. Chronos retains the design integrity of our original, iconic Henry collection, while imbuing it with modern details and exquisite materials.

CODES & STANDARDS

CNS357X, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), DOE, State of MA

PRODUCT FEATURES

Made of Brass

Features a swivel 5" showerhead with three adjustable spray patterns

Includes a 12" wall mounted 90 degree shower arm

Stocked in Brass, Chrome and Nickel

Showerhead available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

Henry Chronos CNS357

Henry Chronos 5" Showerhead with Adjustable Spray with 12" Wall Mounted 90 Degree Shower Arm

