### EASTON

# EA13TF

Easton Vintage Low Profile Concealed Tub Filler With Handshower and White Porcelain Lever Handles



#### **TECHNICAL DETAILS**

ADA Compliance: No Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 38 mm Deck Thickness Minimum: 0 mm Diameter of Head: 76 mm **Escutcheon Primary Material: Brass** Fittings Hole Diameter: 35 mm Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 305 mm Handle Spread Minimum: 254 mm Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 2.0 m Depth / Width: 311 mm Height: 184 mm Index Marking: H/C Inlet Connection Size: 3/4" Inlet Connection Type: Male G/BSPP Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 254 mm Installation Type: Deck Mounted Integrated Diverter: N Length: 457 mm Number of Handles: Two Number of Holes: Four Hole Pivot: N Primary Material: Brass Restricted Maximum Flow Rate: 9.5 liters/min Spout Reach: 10" Spout Swivel: N Suggested Application: Bath Water Pressure Maximum: 5.5 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN EASTON VINTAGE LOW PROFILE CONCEALED TUB FILLER WITH HANDSHOWER AND WHITE PORCELAIN LEVER

### **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods Code # : ASME A112.18.1, CSA B125, ASSE 1014, IAPMO, and a selection of products from fittings to furniture.

#### **CODES & STANDARDS**

State of MA

#### **PRODUCT FEATURES**

Standard flow rate is 2.5gpm for handshower only. Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

# EASTON

## EA13TF

Easton Vintage Low Profile Concealed Tub Filler With Handshower and White Porcelain Lever Handles

