EASTON EA52TF

Easton Classic Gooseneck Concealed Tub Filler With Handshower and Metal Lever Handles



L. SHOWN IN EASTON CLASSIC GOOSENECK CONCEALED TUB FILLER WITH HANDSHOWER AND METAL LEVER HANDLES| EATF52

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

PRODUCT FEATURES

Brass metal is used for all trim and valve components

Optional handle materials include porcelain and semi-precious stones.

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

The pillowed propeller on the cross handle makes the product fit comfortably in the hand. Standard flow rate is 2.5gpm for handshower only. Also available in high efficiency flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

TECHNICAL DETAILS

ADA Compliance: No

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 38 mm

Deck Thickness Minimum: 0 mm

Diameter of Head: 76 mm

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 35 mm

Flow Restriction Options: 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 305 mm

Handle Spread Minimum: 254 mm

Handle Turn Angle: Quarter Turn

Handshower / Spray Hose Length: 2.0 m

Index Color / Finish and Material: White Porcelain

Depth / Width: 305 mm

Height: 222 mm

Index Marking: Hot/Cold

Inlet Connection Size: 3/4"

Inlet Connection Type: Male G/BSPP Inlet Supply Spread Maximum: 305 mm

Inlet Supply Spread Minimum: 254 mm

Installation Type: Deck Mounted

Integrated Diverter: N

Length: 406 mm

Number of Handles: Three

Number of Holes: Five Hole

Pivot: N

Primary Material: Brass

Restricted Maximum Flow Rate: 9.5 liters/min

Spout Reach: 9"

Spout Swivel: N

Suggested Application: Bath

Water Pressure Maximum: 5.5 bar

Water Pressure Minimum: 1.5 bar

Water Pressure Recommended: 3.0 bar

EASTON EA52TF

Easton Classic Gooseneck Concealed Tub Filler With Handshower and Metal Lever Handles

