

DASH

DSKM30

Dash Three Hole Gooseneck Kitchen Faucet with Metal Lever Handles and Spray



SHOWN IN DASH THREE HOLE GOOSENECK KITCHEN FAUCET WITH METAL LEVER HANDLES AND SPRAY| DSKM30

TECHNICAL DETAILS

ADA Compliance: Yes
 Deck Thickness Maximum: 67 mm
 Deck Thickness Minimum: 6 mm
 Escutcheon Primary Material: Brass
 Fitting Hole Configuration / Number: Three
 Fittings Hole Diameter: 35 mm
 Flow Restriction Options: 2.0, 1.75, 1.5
 Handle Spread Maximum: 305 mm
 Handle Spread Minimum: 203 mm
 Handle Turn Angle: Quarter Turn
 Handshower / Spray Hose Length: 1.5 m
 Depth / Width: 313 mm
 Height: 343 mm
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Male with Supply Nut
 Integrated Diverter: Y
 Integrated Spray: Y
 Number of Holes: Four Hole
 Primary Material: Brass
 Restricted Maximum Flow Rate: 8.3 liters/min
 Spray Included in Unit: Y
 Suggested Application: Bar, Kitchen, Laundry
 Valve Material: Ceramic
 Water Pressure Maximum: 6.0 bar
 Water Pressure Minimum: 1.5 bar
 Water Pressure Recommended: 3.0 bar

INSPIRATION

A blend of art and function, Dash pays homage to design elements of the 1930s with pared-down shapes, softened curves and minimal details.

PRODUCT FEATURES

Pared down shapes, softened curves and minimal details inspired by design elements from the 1930's.

10 3/8" Gooseneck swivel spout.

Lever handles.

Integrated diverter to divert water to side spray.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in high efficiency flow options. Contact a sales associate for details.

WATERWORKS

DASH

DSKM30

Dash Three Hole Gooseneck Kitchen Faucet with Metal Lever Handles and Spray

