.25 PTLS01

.25 Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

#### **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 54 mm
Deck Thickness Minimum: 3 mm

Depth/Width: 181 mm

Drain Assembly Materials: Brass Drain Depth Maximum: 44 mm Drain Depth Minimum: 32 mm Drain Hole Diameter: 44 mm Drain Style: Push Touch

Escutcheon Primary Material: Brass Fittings Hole Diameter: 35 mm

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 305 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Height: 102 mm

Inlet Connection Size: 1/2"

Inlet Connection Type: Male With Supply Nut Inlet Supply Spread Maximum: 305 mm Inlet Supply Spread Minimum: 203 mm Installation Type: Deck Mounted

Length: 289 mm

Number Of Handles: Two Number Of Holes: Three Hole Primary Material: Brass Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 6.0 bar

Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

SHOWN IN .25 LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES | PTLS01

### **INSPIRATION**

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful.

### **CODES & STANDARDS**

Code # PTLS01Y-LLX: Complies with ASME A112.18.1/CSA B125.1, cUPC, NSF 61/NSF 372, and ADA. Certified with IAPMO, NSF, CEC, DOE, State of MA, WaterSense, and WRAS.

### PRODUCT FEATURES

TEST updating FS #1

TEST updating FS #2

TEST updating FS #3

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

## **CERTIFICATIONS**









# PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

.25 PTLS01

.25 Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

