EASTON EALS48

Easton Classic Low Profile Three Hole Wall Mounted Lavatory Faucet with Elongated Spout and White Porcelain Lever Handles



### **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 6 1/2"

Drain Assembly Materials: Brass Drain Depth Maximum: 2 3/4" Drain Depth Minimum: 1" Drain Hole Diameter: 1 3/4" Fittings Hole Diameter: 1 3/8" Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Height: 3"

Index Color Finish And Material: White Porcelain

Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Wall Mounted

Length: 15"

Number Of Holes: Three Hole

Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN EASTON CLASSIC LOW PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH ELONGATED SPOUT AND WHITE PORCELAIN LEVER HANDLES | EALS48

#### **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

#### **CODES & STANDARDS**

Code # EALS48: CEC

## **PRODUCT FEATURES**

Available in 1.2gpm (4.5L/min) flow rate

## **CERTIFICATIONS**



## PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

# WATERWORKS

EASTON  Easton Classic Low Profile Three Hole Wall Mounted Lavatory Faucet with Elongated Spout and White Porcelain Lever Handles	EALS48
Handles	