## **HENRY CHRONOS**

**CLS314** 

Henry Chronos Wall Mounted Lavatory Faucet with Walnut Lever Handles



#### **TECHNICAL DETAILS**

ADA Compliance: Yes Drain Depth Maximum: 2" Drain Depth Minimum: 3/8" Drain Hole Diameter: 1 1/2" Drain Style: Push Touch Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Inlet Connection Size: 1/2"

Inlet Connection Type: Female NPT & Male BSPP

Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Valve Material: Brass and Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY CHRONOS WALL MOUNTED LAVATORY FAUCET WITH WALNUT LEVER HANDLES | CLS314

## **INSPIRATION**

Inspired by dive watches, Henry Chronos radiates design prowess and technical precision. Chronos retains the design integrity of our original, iconic Henry collection, while imbuing it with modern details and exquisite materials.

## **CODES & STANDARDS**

CLS314X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, DOE, State of MA

## **PRODUCT FEATURES**

Features Walnut Lever Handles

Includes a Universal Push Touch Drain Sized to Fit US and Euro Sink Drain Openings

Stocked in Brass, Chrome and Nickel

Available in 1.2gpm (4.5L/min) Flow Rate

## CERTIFICATIONS





## PRODUCT (NOTES)

# **HENRY CHRONOS**

**CLS314** 

Henry Chronos Wall Mounted Lavatory Faucet with Walnut Lever Handles

