# WATERWORKS

EASTON EALS50

Easton Classic Low Profile Three Hole Wall Mounted Lavatory Faucet with Elongated Spout and Oak Lever Handles



#### **TECHNICAL DETAILS**

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray Control Valve Rough-in Depth Maximum: 133 mm Control Valve Rough-in Depth Minimum: 70 mm Drain Assembly Materials: Brass

Drain Depth Maximum: 70 mm Drain Hole Diameter: 44 mm Fittings Hole Diameter: 35 mm Handle Spread Maximum: 203 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn

Index Color / Finish and Material: White Porcelain

Depth / Width: 165 mm Drain Depth Minimum: 25 mm Height: 76 mm

Inlet Connection Size: 1/2"
Inlet Connection Type: Male NPT
Inlet Supply Spread Maximum: 203 mm
Inlet Supply Spread Minimum: 203 mm
Installation Type: Wall Mounted
Length: 381 mm

Number of Holes: Three Hole
Primary Material: Brass

Restricted Maximum Flow Rate: 4.5 liters/min Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

L SHOWN IN EASTON CLASSIC LOW PROFILE THREE HOLE WALL MOUNTED LAVATORY FAUCET WITH ELONGATED SPOUT

### **INSPIRATION**

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

## **CODES & STANDARDS**

Code # EALS50: CEC

## PRODUCT FEATURES

Available in 1.2gpm (4.5L/min) flow rate

### CERTIFICATIONS



## PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

EASTON EALS50

Easton Classic Low Profile Three Hole Wall Mounted Lavatory Faucet with Elongated Spout and Oak Lever Handles

