

UNIVERSAL

UNWO25

Universal Push-Touch Tub Drain and Docking Station with Overflow



SHOWN IN UNIVERSAL PUSH-TOUCH TUB DRAIN AND DOCKING STATION WITH OVERFLOW | UNWO25

TECHNICAL DETAILS

Drain Depth Maximum: 51 mm
 Drain Depth Minimum: 35 mm
 Drain Hole Diameter: 51 mm
 Drain Style: Push-Touch
 Fittings Hole Diameter: 102 mm
 Outlet Connection Size: 1 1/2"
 Outlet Connection Type: SCH40 ABS and PVC Socket Adapter
 Overflow Depth Maximum: 51 mm
 Overflow Depth Minimum: 35 mm

INSPIRATION

Featuring enduring designs that complement any Waterworks element, this collection spans fittings to accessories, bringing exquisite proportion and balance to any environment.

CODES & STANDARDS

ASME A112.18.2-2020/CSA B125.2-20

PRODUCT FEATURES

- Designed for heavy tubs with push touch drain and integrated overflow channel
- Installs in standard 1 1/2" DWV pipe
- Supplied with ABS, PVC adapter kits, tools and dust cover
- All Finishes are Special Order
- Drain can be installed from above, without lifting tub

CERTIFICATIONS



PRODUCT (NOTES)

WATERWORKS

UNIVERSAL

UNWO25

Universal Push-Touch Tub Drain and Docking Station with Overflow

