Henry HNXT60

Henry Exposed Floor Mounted Tub Filler With Handshower and Metal Cross Handles



SHOWN IN HENRY EXPOSED FLOOR MOUNTED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES | HNXT60

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

TECHNICAL DETAILS

ADA Compliance: No

Adjustable Versus Fixed Spray: Fixed Spray

Depth/Width: 275 mm Diameter Of Head: 48 mm Diameter Of Legs Tubes: 40 mm Escutcheon Primary Material: Brass Fittings Hole Diameter: 29 mm

Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 203 mm Handle Spread Minimum: 203 mm Handle Turn Angle: Quarter Turn Handshower Spray Hose Length: 1.5 m

Height: 1068 mm

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 203 mm Inlet Supply Spread Minimum: 203 mm

Installation Type: Freestanding Integrated Diverter: N

Integrated Diverter: N
Integrated Spray: N
Number Of Handles: Two
Number Of Holes: Two Hole

Pivot: N

Primary Material: Brass

Spout Swivel: N

Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 6.0 bar Water Pressure Minimum: 1.5 bar Water Pressure Recommended: 3.0 bar

CODES & STANDARDS

ASME A112.18.1/CSA B125.1, Waterworks Handshowers use check valves compliant to ASME A112.18.3 for backflow protection. CEC, State of MA

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing.

Brass material is used for components.

Includes floor unions

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details

CERTIFICATIONS



PRODUCT (NOTES)

Henry HNXT60

Henry Exposed Floor Mounted Tub Filler With Handshower and Metal Cross Handles

