


UNIVERSAL

USH203

Universal Modern 3 1/4" Showerhead with Adjustable Spray



SHOWN IN UNIVERSAL MODERN 3 1/4" SHOWERHEAD WITH ADJUSTABLE SPRAY | USH203

TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Adjustable Spray
 Flow Restriction Options: 1.5, 1.75, 2.0
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Female NPT
 Pivot: Y
 Primary Material: Brass
 Restricted Maximum Flow Rate: 1.75 gpm
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

CODES & STANDARDS

USH203X, ASME A112.18.1/CSA B125.1, CEC(1.5GPM & 1.75GPM Only), WaterSense(1.5GPM, 1.75GPM & 2.0GPM Only), DOE, State of MA

PRODUCT FEATURES

Compatible with an assortment of Waterworks arms and flanges, sold separately

Swiveling 3 1/4" showerhead

Adjustable showerhead features three spray patterns

Stocked in Brass, Chrome and Nickel


Showerhead available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS




PRODUCT (NOTES)


Universal Modern 3 1/4" Showerhead with Adjustable Spray




CEILING VIEW SCALE: 3"=1'-0"



SPRAY PATTERNS



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW

SCALE: 3"=1'-0"